



PRODUCT OVERVIEW

Bio-W™ is the first bio-remedial, floating absorbent designed to absorb and control most hydrocarbons floating on water. This product has the ability to repel water whilst holding onto the hydrocarbons. As the hydrocarbons are locked into the fibres of Bio-W™ absorbent the microbes begin to bio-remediate the contaminant turning the hydrocarbon into harmless carbon dioxide and water. Bio-W™ will float even when saturated with oil and will not leach or drain during the bio-remediation process.

HOW TO USE

Bio-W™ will work well on both fresh and salt water. The following are general directions for use which may be adapted to your own needs.

1. Spread Bio-W evenly over the surface of the water, coving the floating contaminant.
2. It is not necessary to cover all the surface area as Bio-W™ will attract the contaminant.
3. Bio-W™ will float even when it has absorbed all the contaminant.
4. When the contaminant is absorbed, use a rake, net or skimmer to remove all the Bio-W™ from the surface of the water.
5. Place the used Bio-W™ in a plastic bag or container and close the top/lid securely.
6. Leave the Bio-W™ in the container for around 10 days.
7. Dispose of according to local, state and federal regulations.

WHAT IT CAN TREAT

SpillAway Brands Bio-W™ can be used in all phases of manufacturing, commercial and industrial operations. The following is a partial list of the many uses of this product.

Holding Lagoons	Oil Water Separators	Open Water Areas	Retention Basins	Ponds
Construction sites	Manhole Areas	Auto Wash Areas	Drainage Ditches	Trenches

TECHINICAL INFORMATION

Bio-W™ is an active mixture of hydrocarbon-oxidising, naturally occurring single-celled micro-organisms with a natural fibre, hydrophobic absorbent.

Bio-W™ is not hazardous to the environment, it is pH Neutral and biodegradable.

Product Effectiveness: The effectiveness of this product and the speed at which it works is determined by certain factors. In general, these factors are:

- **Temperature:** The warmer the temperature the faster this product will work.
- **Type of Hydrocarbon:** Some hydrocarbons take longer than others.

In our experience that the absorption action of this product begins immediately. The bio-remedial process will begin almost after the introduction of water, but may take longer to complete depending on the above factors.

Appearance	Light Grey Flakes
Odor	None
Boiling Point	N/A
Soluble in Water	Insoluble
pH Concentrate	7.0
pH Diluted	6.9 to 7.9
Evaporation Rate	N/A

PACKAGING INFORMATION

Available in carton: 1 cubic foot
(covers approx. 48 square feet)

For more information on Bio-W and other products from SpillAway Brands™, please contact:

SpillAway Projects Ltd, 37 Underhill, Moulsoford, Oxfordshire, OX10 9JH

Tel: 01491 651392

Email: info@spillawayprojects.co.uk

